## NSN 5305-01-165-4294



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-165-4294 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.588 inches **Fastener Length:** 1.000 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches **Grip Length:** 0.312 inches Thready Qty Per Inch (tpi): 32 **Special Features:** Two keyways along threads 180 degree apart, length of keyways 0.920 in. Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 304l or steel comp 310 or steel comp 316l or steel comp 316l or steel comp 316l or steel comp 305 or steel co comp 317 or steel comp 321 or steel comp 347 or steel comp 309 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5305-01-165-4294

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0