## NSN 5305-01-165-5596



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-165-5596 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.406 inches **Fastener Length:** 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches **Grip Length:** 0.094 inches Thready Qty Per Inch (tpi): 32 **Special Features:** Two keyways along threads 180 degree apart, length of keyways 0.420 in. Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 304l or steel comp 310 or steel comp 316l or steel comp 316l or steel comp 316l or steel comp 305 or steel co comp 317 or steel comp 321 or steel comp 347 or steel comp 309 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

Demilitarization:

**Unit Of Measure:** 

No

N/a

## NSN 5305-01-165-5596

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0