

View Online at <https://aerobasegroup.com/nsn/5305-01-165-7547>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.314 inches and 0.364 inches

Fastener Length:

Between 0.449 inches and 0.479 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.294 inches and 0.332 inches

Grip Diameter:

Between 0.1610 inches and 0.1635 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.164 inches

Grip Length:

Between 0.115 inches and 0.135 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas1221 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0