## NSN 5305-01-165-8608

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-165-8608

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.358 inches and 0.437 inches
Fastener Length:
Between 0.422 inches and 0.469 inches
Head Style:
Dished hexagon
Head Height:
Between 0.105 inches and 0.120 inches
Width Between Flats:
Between 0.305 inches and 0.314 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Criticality Code Justification:
Feat
Screw Material:
Iron alloy 660
Screw Material Specification:
Ms 5731 assn standard single material response or ams 5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Special Features:
Weapons system essential
Thread Series Designator:
Unjf
Specification Data:
80205-nas1802 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-165-8608

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0