NSN 5305-01-165-9161

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-165-9161 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.172 inches **Fastener Length:** 0.500 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.094 inches and 0.098 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.328 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80 pounds per square inch **Externally Relieved Body Diameter Quantity: Special Features:** Make from ms51957-30 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses or aisi assn standard all material responses or sae assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:**

Unc

Shelf Life:

Thread Series Designator:

Mil-f-14072-e300 military specification single treatment response

N/a

NSN 5305-01-165-9161

Externally Relieved Body Screw - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072-e300 spec.