Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-166-3641

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.360 inches and 0.390 inches
Fastener Length:
1.000 inches
Head Style:
Hexagon
Head Height:
Between 0.150 inches and 0.161 inches
Width Between Flats:
Between 0.4280 inches and 0.4375 inches
First Diameter From Head:
Between 0.180 inches and 0.190 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.625 inches
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
2910 pounds per square inch
Externally Relieved Body Diameter Quantity:
1
Material:
Stainless steel
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 type 2 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5305-01-166-3641

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

