

View Online at <https://aerobasegroup.com/nsn/5305-01-166-4415>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.127 inches and 1.250 inches

Fastener Length:

Between 1.210 inches and 1.250 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.457 inches and 0.469 inches

Head Height:

Between 0.306 inches and 0.313 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.312 inches

Width Across Flats:

Between 0.250 inches and 0.251 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

170000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

150000 pounds per square inch

Special Features:

Color black

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 303

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 cl4 military specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

6 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.