NSN 5305-01-166-5722

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-166-5722 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.170 inches **Fastener Length:** 0.562 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.314 inches **Head Height:** 0.115 inches **First Diameter From Head:** 0.120 inches **Second Diameter From Head:** 0.164 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.392 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.562 inches **Point Style:** Flat **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Askewed Head Angle:** 90.0 degrees **Externally Relieved Body Diameter Quantity:** 2 Material: Stainless steel **Material Specification:**

Surface Treatment: Passivate

Qq-s-761 federal specification single material response

NSN 5305-01-166-5722

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0