NSN 5305-01-166-6140

Close Tolerance Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-166-6140

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.400 inches an	nd 0.450 inches
Fastener Length:	
Between 1.722 inches ar	nd 1.752 inches
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.455 inches ar	nd 0.510 inches
Grip Diameter:	
Between 0.2485 inches a	and 0.2495 inches
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.250 inches	
Grip Length:	
Between 1.302 inches ar	nd 1.322 inches
Thready Qty Per Inch (f	ːpi):
28	
Countersink Angle:	
Between 99.0 degrees a	nd 101.0 degrees
Surface Finish:	
32.0 microinches threads	3
Material:	
Steel comp e4340 or ste	el comp 8740
Material Specification:	
Mil-s-5000 military specif	fication 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Spe	cification:
Qq-p-416 type 2 class 2	federal specification single treatment response
Thread Series Designation	tor:
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

No

NSN 5305-01-166-6140

Close Tolerance Screw - Page 2 of 2

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.

