NSN 5305-01-166-6643

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-166-6643

| The state of the s |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.296 inches and 0.437 inches |
| Fastener Length: |
| Between 0.422 inches and 0.469 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.096 inches and 0.110 inches |
| Width Between Flats: |
| Between 0.241 inches and 0.250 inches |
| Hole Diameter: |
| Between 0.035 inches and 0.045 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.164 inches |
| Hole Quantity: |
| 2 |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Hardness Rating: |
| Between 26.0 rockwell c and 32.0 rockwell c |
| Screw Material: |
| Steel comp 4037 or steel comp 8630 |
| Screw Material Specification: |
| Ams6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response |
| Head Hole Configuration Style: |
| Round |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5305-01-166-6643

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.