NSN 5305-01-166-6643

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-166-6643

The state of the s
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.296 inches and 0.437 inches
Fastener Length:
Between 0.422 inches and 0.469 inches
Head Style:
Hexagon
Head Height:
Between 0.096 inches and 0.110 inches
Width Between Flats:
Between 0.241 inches and 0.250 inches
Hole Diameter:
Between 0.035 inches and 0.045 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.164 inches
Hole Quantity:
2
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
Between 26.0 rockwell c and 32.0 rockwell c
Screw Material:
Steel comp 4037 or steel comp 8630
Screw Material Specification:
Ams6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response
Head Hole Configuration Style:
Round
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-166-6643

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.