## NSN 5305-01-167-2398

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-167-2398

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.376 inches and 0.438 inches
Fastener Length:
Between 0.407 inches and 0.438 inches
Head Style:
Pan
Head Diameter:
Between 0.306 inches and 0.322 inches
Head Height:
Between 0.105 inches and 0.115 inches
Locking Feature:
Pellet or strip
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Locking Feature Material:
Plastic polychlorotrifluoroethylene
Screw Material Specification:
Ams 5737 assn standard single material response
Locking Feature Material Specification:
Ams 3650 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-167-2398

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0