## NSN 5305-01-167-2406

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-167-2406

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.505 inches and 0.572 inches
Fastener Length:
Between 1.827 inches and 1.874 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.602 inches and 0.634 inches
Head Height:
Between 0.0878 inches and 0.0899 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.312 inches
Grip Length:
Between 1.302 inches and 1.322 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Special Features:
Furnished with o-ring
Material:
Titanium alloy uns r54520
Material Specification:
Ams 4967 assn standard single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-167-2406

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0