NSN 5305-01-167-4350

Close Tolerance Screw - Page 1 of 2

3a

28





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.378 inches and 0.428 inches Fastener Length: Between 0.950 inches and 0.980 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.464 inches and 0.507 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches Grip Length: Between 0.552 inches and 0.572 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator: Specification Data:** 80205-nas1580 professional/industrial association standard Shelf Life:

N/a

Unjf

NSN 5305-01-167-4350

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

