## NSN 5305-01-167-9406

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-167-9406 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.865 inches and 0.885 inches **Fastener Length:** Between 1.060 inches and 1.080 inches **Head Diameter:** Between 0.432 inches and 0.442 inches **Head Height:** Between 0.240 inches and 0.260 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Primary Washer Outside Diameter:** Between 0.615 inches and 0.635 inches **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 0.050 inches and 0.070 inches Material: Steel comp 4130 **Material Specification:** Mil-s-6758, cond d-4 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-01-167-9406

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.