## NSN 5305-01-168-0869

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-168-0869

| Thread Class:   |
|---|
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 1.758 inches and 2.000 inches   |
| Fastener Length:  |
| Between 1.940 inches and 2.000 inches   |
| Head Style:   |
| Flat chamfer  |
| Head Diameter:  |
| Between 0.921 inches and 0.938 inches   |
| Head Height:  |
| Between 0.616 inches and 0.625 inches   |
| Locking Feature:  |
| Strip threads or pellet threads or patch threads                                |
| Internal Drive Style:   |
| Hexagon   |
| Thread Diameter:  |
| 0.625 inches  |
| Width Across Flats:   |
| 0.500 inches  |
| Thready Qty Per Inch (tpi):   |
| 11  |
| Min. Tensile Strength (psi):  |
| 170000 pounds per square inch   |
| Hardness Rating:  |
| 38.0 rockwell c and 45.0 rockwell c   |
| Minimum Yield Strength:   |
| 150000 pounds per square inch   |
| Material:   |
| Steel fastener  |
| Material Specification:   |
| Astm a574 assn standard single material response fastener                       |
| Surface Treatment:  |
| Phosphate fastener  |
| Surface Treatment Specification:  |
| Mil-p-16232 ty z cl 2 military specification single treatment response fastener |
| Thread Series Designator:   |
| Unc   |
| Specification Or Standard:  |
| 6 type  |
|   |

## NSN 5305-01-168-0869

Socket Head Cap Screw - Page 2 of 2



| N/a               |  |
|-------------------|--|
| Unit Of Measure:  |  |
|                   |  |
| Demilitarization: |  |
| No                |  |
| Fiig:             |  |
| A003b0            |  |

Mil-std (military Standard):

Mil-p-16232 spec.

Shelf Life: