NSN 5305-01-168-0869

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-168-0869

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 1.758 inches and 2.000 inches
Fastener Length:
Between 1.940 inches and 2.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.921 inches and 0.938 inches
Head Height:
Between 0.616 inches and 0.625 inches
Locking Feature:
Strip threads or pellet threads or patch threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.625 inches
Width Across Flats:
0.500 inches
Thready Qty Per Inch (tpi):
11
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
150000 pounds per square inch
Material:
Steel fastener
Material Specification:
Astm a574 assn standard single material response fastener
Surface Treatment:
Phosphate fastener
Surface Treatment Specification:
Mil-p-16232 ty z cl 2 military specification single treatment response fastener
Thread Series Designator:
Unc
Specification Or Standard:
6 type

NSN 5305-01-168-0869

Socket Head Cap Screw - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-p-16232 spec.

Shelf Life: