Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-168-0870



Thread Class: 2a **Thread Direction: Right-hand Thread Length:** Between 0.512 inches and 0.625 inches Fastener Length: Between 0.595 inches and 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches Locking Feature: Strip threads or pellet threads or patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 155000 pounds per square inch Material: Steel fastener **Material Specification:** Astm a574 assn standard single material response fastener Surface Treatment: Phosphate fastener and zinc fastener **Surface Treatment Specification:** Dod-p-16232 ty z cl 2 military specification single treatment response fastener **Thread Series Designator:** Unc **Specification Or Standard:** 6 type

NSN 5305-01-168-0870

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

spec.

