

View Online at <https://aerobasegroup.com/nsn/5305-01-168-1201>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.240 inches and 0.282 inches

Fastener Length:

Between 0.282 inches and 0.312 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.176 inches and 0.183 inches

Head Height:

Between 0.108 inches and 0.112 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.112 inches

Width Across Flats:

Between 0.094 inches and 0.095 inches

Thready Qty Per Inch (tpi):

48

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Product Name:

Navy special project

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384

Material Specification:

66 assn standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0