## NSN 5305-01-168-4480

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-168-4480 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 2.455 inches **Fastener Length:** Between 3.145 inches and 3.205 inches **Head Style:** Pan **Head Diameter:** 0.310 inches **Head Height:** 0.090 inches **First Diameter From Head:** Between 0.143 inches and 0.153 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.720 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.189 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Color black Material: Steel comp 303 or steel comp 303se or steel comp 303ma or steel comp 303pb or steel comp 303 plus x **Material Specification:** Astm a582 assn standard all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl 2 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-168-4480

Externally Relieved Body Screw - Page 2 of 2



_		 • •				
n	em	it o	riz	<b>2</b> †1	n	٠.

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.