NSN 5305-01-168-4482

Thread Class:

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-168-4482

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.837 inches and 0.938 inches
Fastener Length:
Between 0.908 inches and 0.938 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.244 inches and 0.250 inches
Hole Diameter:
Between 0.044 inches and 0.050 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.187 inches and 0.190 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

NSN 5305-01-168-4482

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0