## NSN 5305-01-168-7236

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-168-7236 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.336 inches **Fastener Length:** 0.398 inches **Head Style:** Hexagon **Head Height:** 0.040 inches Width Between Flats: 0.188 inches **First Diameter From Head:** 0.062 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.062 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 42.0 rockwell c and 45.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Hexagon socket in threaded end. Width across flats 0.050 min and 0.051 max Material: Steel comp 4140 **Material Specification:** Astm a322 assn standard single material response or astm a331 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** 

Unc

**Thread Series Designator:** 

Qq-p-416, type 2 cl 1 federal specification single treatment response

## NSN 5305-01-168-7236

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0