NSN 5305-01-168-7738

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-168-7738 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.235 inches and 0.265 inches **Fastener Length:** Between 0.395 inches and 0.425 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.299 inches and 0.329 inches **Head Height:** Between 0.076 inches and 0.106 inches **Internal Drive Style:** Cross recess type 1 **Material Accommodated Thickness:** Between 0.063 inches and 0.125 inches **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 384 fastener or steel comp 385 fastener **Material Specification:** Qq-a-225/8 federal specification single material response stand-off **Surface Treatment:** Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response fastener **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

Mil-a-8625 spec.

Mil-std (military Standard):

A003b0