NSN 5305-01-169-3186

Thread Class:

Right-hand

Thread Length:

Thread Direction:

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-169-3186

Between 1.440 inches and 1.810 inches
Fastener Length:
Between 4.940 inches and 5.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.368 inches and 0.375 inches
Hole Diameter:
Between 0.061 inches and 0.067 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.312 inches and 0.316 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
150000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 class 3 federal specification single treatment response

NSN 5305-01-169-3186

Socket Head Cap Screw - Page 2 of 2



Inread Series Designator:
Unc
Specification Or Standard:
6 type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0