NSN 5305-01-169-6384

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-169-6384

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.422 inches and 1.531 inches
Fastener Length:
Between 1.484 inches and 1.531 inches
Head Style:
Hexagon
Head Height:
Between 0.105 inches and 0.120 inches
Width Between Flats:
Between 0.305 inches and 0.314 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Hole Quantity:
3
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Steel comp e4340 or steel comp 8740
Screw Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416 type 2 class 2 federal specification single treatment response
Head Hole Configuration Style:
Hexagon corners
Thread Series Designator:
Unjf
Specification Data:

80205-nas1801 professional/industrial association standard

NSN 5305-01-169-6384

Machine Screw - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
i iig.	

Mil-std (military Standard):

Mil-s-5000 spec.

Shelf Life: