## NSN 5305-01-169-6774

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-169-6774

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.400 inches and 0.450 inches
Fastener Length:
Between 1.035 inches and 1.065 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.449 inches and 0.507 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Grip Length:
Between 0.615 inches and 0.635 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Countersink Angle:
Countersink Angle: Between 99.0 degrees and 101.0 degrees
Between 99.0 degrees and 101.0 degrees
Between 99.0 degrees and 101.0 degrees  Material:
Between 99.0 degrees and 101.0 degrees  Material:  Iron alloy 660
Between 99.0 degrees and 101.0 degrees  Material:  Iron alloy 660  Material Specification:
Between 99.0 degrees and 101.0 degrees  Material: Iron alloy 660  Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Between 99.0 degrees and 101.0 degrees  Material: Iron alloy 660  Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response  Surface Treatment:
Between 99.0 degrees and 101.0 degrees  Material:  Iron alloy 660  Material Specification:  Ams 5731 assn standard single material response or ams 5737 assn standard single material response  Surface Treatment:  Cadmium and chromate
Between 99.0 degrees and 101.0 degrees  Material: Iron alloy 660  Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response  Surface Treatment: Cadmium and chromate  Surface Treatment Specification:
Between 99.0 degrees and 101.0 degrees  Material: Iron alloy 660  Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response  Surface Treatment: Cadmium and chromate  Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response
Between 99.0 degrees and 101.0 degrees  Material: Iron alloy 660  Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response  Surface Treatment: Cadmium and chromate  Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response  Thread Series Designator:
Between 99.0 degrees and 101.0 degrees  Material: Iron alloy 660  Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response  Surface Treatment: Cadmium and chromate  Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response  Thread Series Designator: Unjf

N/a

## NSN 5305-01-169-6774

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0