## NSN 5305-01-169-7223

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-169-7223



### **Thread Class:**

3a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 0.138 inches and 0.230 inches

#### Fastener Length:

Between 0.280 inches and 0.310 inches

#### **Head Style:**

Flat countersunk

#### Head Diameter:

Between 0.371 inches and 0.385 inches

#### Internal Drive Style:

Cross recess type 1

## Thread Diameter:

0.190 inches

## Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

125000 pounds per square inch

## Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### **Product Name:**

Navy special project

#### Screw Material:

Steel comp 4037 or steel comp 8630

#### Screw Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response

#### Screw Surface Treatment:

Cadmium and chromate

#### Screw Surface Treatment Specification:

Qq-p-416, type 2 class 3 federal specification single treatment response

## Thread Series Designator:

Unf

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5305-01-169-7223

Machine Screw - Page 2 of 2

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

