

View Online at <https://aerobasegroup.com/nsn/5305-01-169-7225>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.433 inches and 0.500 inches

Fastener Length:

Between 0.469 inches and 0.500 inches

Head Style:

Fillister

Head Diameter:

Between 0.124 inches and 0.140 inches

Head Height:

Between 0.055 inches and 0.062 inches

Internal Drive Style:

Slot

Thread Diameter:

0.086 inches

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

55000 pounds per square inch

Screw Material:

Copper alloy 268 or copper alloy 260 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 353 or copper alloy 270 or copper alloy 274 or copper alloy 464 or copper alloy 462 or copper alloy 482 or copper alloy 485 or copper alloy 210 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 or copper alloy 240 or copper alloy 342

Thread Series Designator:

Unc

Specification Or Standard:

1 type and 4s style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0