

View Online at <https://aerobasegroup.com/nsn/5305-01-169-7237>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.263 inches and 0.314 inches

Fastener Length:

Between 1.685 inches and 1.705 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.095 inches and 0.110 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Locking Feature:

Detent ball grip

Grip Diameter:

Between 0.1889 inches and 0.1894 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Grip Length:

Between 1.312 inches and 1.328 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

63000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.595 inches first hole and 1.615 inches first hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp 630 spring or steel comp 302 spring

Material Specification:

Ams 5629 assn standard single material response fastener

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0