

View Online at <https://aerobasegroup.com/nsn/5305-01-169-8256>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.395 inches and 0.446 inches

Fastener Length:

Between 3.083 inches and 3.103 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.251 inches and 0.266 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Locking Feature:

Detent ball grip

Grip Diameter:

Between 0.4986 inches and 0.4991 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.500 inches

Grip Length:

Between 2.438 inches and 2.454 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

63000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.951 inches first hole and 2.971 inches first hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp 632 fastener

Material Specification:

Ams 5629 assn standard single material response fastener

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0