NSN 5305-01-169-9420

Shoulder Screw - Page 1 of 2

3a

32

View Online at https://aerobasegroup.com/nsn/5305-01-169-9420



Thread Class: Thread Direction: Right-hand Thread Length: Between 0.338 inches and 0.388 inches Fastener Length: Between 1.098 inches and 1.128 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.381 inches Shoulder Diameter: 0.204 inches first shoulder and 0.205 inches first shoulder Shoulder Length: 0.740 inches first shoulder and 0.760 inches first shoulder **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1580 professional/industrial association standard Shelf Life:

N/a

NSN 5305-01-169-9420

Shoulder Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

