NSN 5305-01-169-9608

Machine Screw - Page 1 of 2

Between 0.533 inches and 0.573 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5305-01-169-9608

Fastener Length:
Between 0.615 inches and 0.635 inches
Head Style:
Double hexagon w/ hole
Head Height:
Between 0.220 inches and 0.240 inches
Width Between Flats:
Between 0.2088 inches and 0.2288 inches
Extended Washer Diameter:
Between 0.302 inches and 0.322 inches
Extended Washer Thickness:
0.030 inches
Hole Diameter:
0.047 inches
Thread Diameter:
0.164 inches
Hole Quantity:
4
Thready Qty Per Inch (tpi):
36
Min. Tensile Strength (psi):
130000 pounds per square inch
Hardness Rating:
Between 24.0 rockwell c and 35.0 rockwell c
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5731 assn standard single material response
Screw Surface Treatment:
Silver
Screw Surface Treatment Specification:
Ams 2411 assn standard single treatment response
Head Hole Configuration Style:
Double hexagon longitudinal hole
Precious Material And Location:
silver

NSN 5305-01-169-9608

Machine Screw - Page 2 of 2



Precious Material:
Silver
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A500d0