## NSN 5305-01-169-9611



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-169-9611 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.338 inches and 0.388 inches **Fastener Length:** Between 1.160 inches and 1.190 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.381 inches **Shoulder Diameter:** 0.2197 inches first shoulder and 0.2207 inches first shoulder **Shoulder Length:** 0.802 inches first shoulder and 0.822 inches first shoulder **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1580 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## **NSN 5305-01-169-9611** Shoulder Screw - Page 2 of 2



Fiig:

A003b0