NSN 5305-01-170-1350

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-170-1350



Three	d Class:
3a	
	d Direction:
Right-	
•	d Length:
	en 0.596 inches and 0.646 inches
	ner Length:
	en 1.481 inches and 1.511 inches
Head	
	puntersunk
Head	Diameter:
Betwe	en 0.717 inches and 0.760 inches
Grip [Diameter:
Betwe	en 0.3740 inches and 0.3745 inches
Intern	al Drive Style:
High-t	orque
Threa	d Diameter:
0.375	inches
Grip L	ength:
Betwe	en 0.865 inches and 0.885 inches
Threa	dy Qty Per Inch (tpi):
24	
Min. T	ensile Strength (psi):
16000	0 pounds per square inch
Count	ersink Angle:
Betwe	en 99.0 degrees and 101.0 degrees
Surfa	ce Finish:
32.0 n	nicroinches threads
Mater	ial:
Iron al	loy 660
Mater	ial Specification:
Ams5	731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
materi	al response
Surfa	ce Treatment:
Passiv	vate
Surfa	ce Treatment Specification:
Qq-p-3	35 federal specification single treatment response
Threa	d Series Designator:
Unjf	
Speci	fication Data:
80205	-nas1580 professional/industrial association standard
Shelf	Life:

N/a

NSN 5305-01-170-1350

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

