# NSN 5305-01-170-5563

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-170-5563

Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.812 inches

#### Fastener Length:

Between 1.222 inches and 1.233 inches

## Head Style:

Pan no. 2

Head Diameter:

Between 0.357 inches and 0.373 inches

## **Head Height:**

Between 0.099 inches and 0.110 inches

## Internal Drive Style:

Slot

## Material Accommodated Thickness:

Between 0.313 inches and 0.375 inches

## Thread Diameter:

0.190 inches

## Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

140000 pounds per square inch

Material:

Steel comp 302 spring

## **Material Specification:**

Qq-w-423, cond b federal specification single material response spring

## Surface Treatment:

Passivate spring

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spring

## **Thread Series Designator:**

Unf

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A003b0

NSN 5305-01-170-5563

Panel Screw Assembly - Page 2 of 2

## Mil-std (military Standard):

Mil-s-5059 spec.

