Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-170-6132

| 2a                    |  |
|-----------------------|--|
| Thread Direction:     |  |
| Right-hand            |  |
| Thread Length:        |  |
| Between 1.430 inch    | es and 1.490 inches  |
| Fastener Length:      |  |
| Between 2.720 inch    | es and 2.780 inches  |
| Head Style:           |  |
| Hexagon               |  |
| First Diameter Fro    | m Head:  |
| Between 0.803 inch    | les and 0.819 inches   |
| Distance From Lar     | gest Bearing Surface Of Head To End Of First Diameter:   |
| 1.290 inches          |  |
| Internal Drive Style  | 8:   |
| W/o internal drive    |  |
| Thread Diameter:      |  |
| 1.000 inches          |  |
| Thready Qty Per Ir    | nch (tpi):   |
| 8                     |  |
| Criticality Code Ju   | stification:   |
| Zzzy                  |  |
| Externally Relieve    | d Body Diameter Quantity:  |
| 1                     |  |
| Material:             |  |
| Steel comp 304        |  |
| Material Specificat   | ion:   |
| Aisi 304 assn stand   | ard single material response   |
| Thread Series Des     | ignator:   |
| Unc                   |  |
| Reference Numbe       | r Differentiating Characteristics:   |
| Material will be in a | ccordance with ships parts control center activity hx quality control, manufacturing and testing specification |
| Shelf Life:           |  |
| N/a                   |  |
| Unit Of Measure:      |  |
|                       |  |
| Demilitarization:     |  |
| No                    |  |
| Fiig:                 |  |
| A003b0                |  |