

View Online at <https://aerobasegroup.com/nsn/5305-01-170-6150>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.674 inches and 0.849 inches

**Fastener Length:**

Between 0.985 inches and 1.015 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.703 inches and 0.763 inches

**Locking Feature:**

Strip threads or pellet threads or patch threads

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 8740 fastener or steel comp 8735 fastener or steel comp 6150 fastener

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1219 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0