

View Online at <https://aerobasegroup.com/nsn/5305-01-170-6184>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.320 inches and 0.340 inches

Fastener Length:

Between 0.552 inches and 0.572 inches

Head Style:

Hexagon

Head Height:

0.055 inches

Width Between Flats:

0.185 inches

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Special Features:

Color black

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 or steel comp 302b or steel comp 303 plus x or steel comp 303cu or steel comp 303ma

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 class 4 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.