NSN 5305-01-170-8489

Close Tolerance Screw - Page 1 of 1





View Online at https://aerobasegroup.com/nsn/5305-01-170-8489

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.382 inches and 0.412 inches |
| Fastener Length: |
| Between 1.070 inches and 1.100 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.464 inches and 0.507 inches |
| Grip Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| 0.688 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams5629 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| Fiig. A003b0 |
| |