

View Online at <https://aerobasegroup.com/nsn/5305-01-171-0537>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.133 inches and 0.188 inches

**Fastener Length:**

Between 0.158 inches and 0.188 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.091 inches and 0.096 inches

**Head Height:**

Between 0.057 inches and 0.060 inches

**Locking Feature:**

Strip threads or pellet threads or patch threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.060 inches

**Width Across Flats:**

Between 0.050 inches and 0.051 inches

**Thready Qty Per Inch (tpi):**

80

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unrf

**Specification Data:**

80205-nas1351 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0