## NSN 5305-01-171-0556

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-171-0556 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.515 inches **Fastener Length:** Between 0.818 inches and 0.828 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.072 inches and 0.082 inches **Internal Drive Style:** Slot **Material Accommodated Thickness:** Between 0.031 inches and 0.062 inches **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Steel comp 302 spring **Material Specification:** Qq-w-423, cond b federal specification single material response spring **Surface Treatment:** Passivate spring **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spring **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A003b0

## NSN 5305-01-171-0556

Panel Screw Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-s-5059 spec.