NSN 5305-01-171-3412

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-171-3412



| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.157 inches and 0.250 inches |
| Fastener Length: |
| Between 0.219 inches and 0.250 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.221 inches and 0.226 inches |
| Head Height: |
| Between 0.074 inches and 0.086 inches |
| Locking Feature: |
| Strip threads |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.138 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 40.0 rockwell c |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416 type 2 cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjc |
| Specification Data: |
| 80205-nas1191 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5305-01-171-3412

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

