## NSN 5305-01-171-3413

Setscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-171-3413

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.282 inches
Fastener Length:
1.907 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.746 inches and 0.749 inches
Head Height:
Between 0.053 inches and 0.073 inches
Point Length:
1.844 inches
Point Diameter:
0.438 inches
Point Style:
Chamfer dog
Internal Drive Style:
Hexagon
Thread Diameter:
0.562 inches
Width Across Flats:
Between 0.250 inches and 0.252 inches
Thready Qty Per Inch (tpi):
18
Hardness Rating:
240.0 brinell standard and 280.0 brinell standard
Point Chamfer Angle:
90.0 degrees
Special Features:
Furnish with one hole in bottom of point o.125 inch dia. First dia. Length under head 0.093 inch . Second dia. Under head 0.497 inch and
0.093 inch in length
Material:
Steel comp 4140
Material Specification:
Od8853 type d grade 1 class c fscm 10001 mfr ref single material response or astm a304 assn standard single material response or astm
a322 assn standard single material response

## Поэрнате

**Surface Treatment:** 

Phosphate

## **Surface Treatment Specification:**

Dod-p-16232 type m class 2 military specification single treatment response

## NSN 5305-01-171-3413

Setscrew - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

spec.