NSN 5305-01-171-3613

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-171-3613

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.444 inches and 0.494 inches
Fastener Length:
Between 1.266 inches and 1.296 inches
Head Style:
Pan
Head Diameter:
Between 0.568 inches and 0.593 inches
Head Height:
Between 0.162 inches and 0.183 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Single Shear Strength:
108000 pounds per square inch
Internal Drive Style:
High-torque
Thread Diameter:
0.312 inches
Grip Length:
Between 0.802 inches and 0.822 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:

80205-nas1985 professional/industrial association standard

NSN 5305-01-171-3613

Close Tolerance Screw - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0