NSN 5305-01-171-3981

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-171-3981
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.338 inches and 0.388 inches
Fastener Length:
Between 0.973 inches and 1.003 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.339 inches and 0.381 inches
Shoulder Diameter:
0.2041 inches first shoulder and 0.2051 inches first shoulder
Shoulder Length:
0.615 inches first shoulder and 0.635 inches first shoulder
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-171-3981

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0