## NSN 5305-01-172-2548

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-172-2548						
Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.251 inches and 0.301 inches						
Fastener Length:						
Between 0.886 inches and 0.916 inches						
Head Style:						
Flat countersunk						
Head Diameter:						
Between 0.328 inches and 0.385 inches						
Grip Diameter:						
Between 0.1885 inches and 0.1895 inches						
Internal Drive Style:						
Offset cruciform (torque set)						
Thread Diameter:						
0.190 inches						
Grip Length:						
Between 0.615 inches and 0.635 inches						
Thready Qty Per Inch (tpi):						
32						
Min. Tensile Strength (psi):						
160000 pounds per square inch						
Countersink Angle:						
Between 99.0 degrees and 101.0 degrees						
Surface Finish:						
32.0 microinches threads						
Material:						
Iron alloy 660						
Material Specification:						
Ams5737 assn standard single material response						
Surface Treatment:						
Cadmium and chromate						
Surface Treatment Specification:						
Qq-p-416, ty2, cl 2 federal specification single treatment response						
Thread Series Designator:						
Unjf						
Specification Data:						
80205-nas1153 professional/industrial association standard						
Shelf Life:						

N/a

## NSN 5305-01-172-2548

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0