## NSN 5305-01-172-5548

Machine Screw - Page 1 of 1

No Fiig: A500d0



View Online at https://aerobasegroup.com/nsn/5305-01-172-5548 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.440 inches and 1.585 inches **Fastener Length:** Between 1.688 inches and 1.750 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.670 inches and 0.762 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316 or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 **Thread Series Designator:** Unf **Specification Or Standard:** 3 type and 3c style Shelf Life: N/a **Unit Of Measure: Demilitarization:**