NSN 5305-01-172-5556

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-172-5556



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.313 inches and 0.363 inches Fastener Length: Between 1.385 inches and 1.415 inches **Head Style:** Pan **Head Diameter:** Between 0.331 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.132 inches Locking Feature: Patch threads or pellet threads or strip threads **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads **Product Name:** Navy special project Material: Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 8740 fastener or steel comp 8735 fastener or steel comp 6150 fastener Surface Treatment: Cadmium fastener and chromate fastener Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response fastener **Thread Series Designator:**

Unjf

NSN 5305-01-172-5556

Close Tolerance Screw - Page 2 of 2



Specification Data:

80205-nas1173 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0