NSN 5305-01-172-5557

Thread Class:

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-172-5557

Thread Direction:
Right-hand
Thread Length:
Between 1.001 inches and 1.125 inches
Fastener Length:
Between 1.063 inches and 1.125 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.306 inches and 0.313 inches
Head Height:
Between 0.103 inches and 0.118 inches
Locking Feature:
Strip threads or pellet threads or patch threads
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 160000 pounds per square inch
160000 pounds per square inch
160000 pounds per square inch Surface Finish:
160000 pounds per square inch Surface Finish: 32.0 microinches threads
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name:
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material:
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification:
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment:
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data:
160000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1191 professional/industrial association standard

NSN 5305-01-172-5557

Socket Head Cap Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0