NSN 5305-01-173-3513

Machine Screw - Page 1 of 2

A500d0



View Online at https://aerobasegroup.com/nsn/5305-01-173-3513

view Offiline at https://aerobasegroup.com/nsi//0000-01-1/10-0010
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.238 inches and 0.310 inches
Fastener Length:
Between 0.280 inches and 0.310 inches
Head Style:
Pan
Head Diameter:
Between 0.205 inches and 0.219 inches
Head Height:
Between 0.070 inches and 0.080 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
48
Min. Tensile Strength (psi):
62000 pounds per square inch
Screw Material:
Aluminum alloy 2024
Screw Material Specification:
Qq-a-200/3 federal specification single material response or qq-a-225/6 federal specification single material response
Screw Surface Treatment:
Anodize
Screw Surface Treatment Specification:
Mil-a-8625 type 1 military specification single treatment response or mil-a-8625 type 2 cl 1 military specification single treatment response
Thread Series Designator:
Unf
Specification Or Standard:
3 type and 9c style
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

NSN 5305-01-173-3513

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.